



Oil Pattern Distance	43	Reverse Brush Drop	43	Oil Per Board	50
orward Oil Total	22.35 mL	Reverse Oil Total	13.1 mL	Volume Oil Total	35.45 n
ank Configuration	ALT	Tank A Conditioner	PRODIGY	Tank B Conditioner	PRODIC
	ROSSED START END				
1 2L 2R 1 10 2 4L 4R 2 10	37 0.0 0.0 66 0.0 2.8				
3 6L 6R 2 10	58 2.8 5.6				
4 7L 7R 2 14	54 5.6 9.5			~ 6 ~ 8 2	e ~
58L8R 214	50 9.5 13.4	3.9 2500			
69L9R 214	46 13.4 17.3				
7 10L 10R 2 14	42 17.3 21.2				
8 11L 11R 2 18	38 21.2 26.3				<u> </u>
9 12L 12R 1 18 0 13L 13R 1 18	17 26.3 28.8 15 28.8 31.3				
1 14L 14R 1 18	13 31.3 33.8				
12 15L 15R 1 22	11 33.8 36.9				5
13 2L 2R 0 30	0 36.9 43.0	6.1 0			
					
START STOP LOADS SPEED CF	ROSSED START END	FEET T.OIL			
1 2L 2R 0 30	0 43.0 39.0				╞╞┼╞┼┝┝┝┝
2 15L 15R 2 22	22 39.0 32.8				
3 14L 14R 2 18 4 13L 13R 2 18	26 32.8 27.7 30 27.7 22.6				
5 12L 12R 2 14	34 22.6 18.7				╎╎╎╎╎╎╎╎╎ ╞
6 11L 11R 1 14	19 18.7 16.8				
7 10L 10R 1 14	21 16.8 14.9	-1.9 1050			
89L9R 114	23 14.9 13.0	-1.9 1150			╞┼┼┼┼┼┼┼┝╴╞
98L8R 110	25 13.0 11.6				
10 6L 6R 1 10	29 11.6 10.2				
11 4L 4R 1 10 12 2L 2R 0 10	33 10.2 8.8 0 8.8 0.0				<mark>┼┼┼┼┼┼┼┼</mark> ╞
12 2L 2R 0 10	0 8.8 0.0	0 -8.8 0			
					 >
leaner Ratio Main Mix		NA Forward			
					╞╋╋╃┼┼┼┼┼┼┼╴
Cleaner Ratio Back End Mix	[NA Reverse			
leaner Ratio Back End Dist	tance	NA Combined			
ouffer RPM: 4 = 700 3 = 5	00 2 = 200 1	= 100			
			-		╺

